

Spec Sheet

### 4 Port Black SuperSpeed USB 3.0 Hub

StarTech ID: ST4300USB3



The ST4300USB3 4-Port SuperSpeed USB 3.0 Hub allows you to add 4 additional USB 3.0 ports from a single USB 3.0 connection to the host computer system.

Backward compatible with USB 2.0 and USB 1.x standards, this USB 3.0 hub still supports older USB devices and can also be used as a hub on older systems that do not have USB 3.0 ports.

With the capability to mix and match USB 3.0/2.0/1.x devices and be used with or without the included external power adapter, this hub offers the best of versatility and portability.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Applications

- Expand your system USB 3.0 capabilities with additional ports
- Make hard to access USB ports more accessible, by being able to position the hub anywhere the cable will reach
- Extend the range of a USB device by having the hub act as a mid-point repeater





#### Features

- Four USB type A ports that can each be accessed simultaneously
- SuperSpeed USB 3.0 compliant, with data transfer rates up to 5 Gbps
- Backward compatible with USB 2.0 and USB 1.0/1.1 specifications and devices
- Supports USB 3.0/2.0/1.x devices simultaneously, at full bandwidth
- Provides up to 900mA of power per port to a maximum of 2900mA total
- Compact, desktop-style form factor
- Plug-and-Play and hot-swap compatible

www.startech.com/au 1800 808 346

# StarTechcom

Hard-to-find made easy®

## Spec Sheet

### **Technical Specifications**

Warranty	2 Years
Color	Black
Enclosure Type	Plastic
Product Height	0.9 in [23 mm]
Product Length	3.7 in [95 mm]
Product Weight	1.9 oz [55 g]
Product Width	2.7 in [68 mm]
Chipset ID	VLI - VL810
Interface	USB 3.0
Ports	4
Maximum Data Transfer Rate	5 Gbps
External Ports	1 - USB 3.0 B (9 pin; SuperSpeed) Female
External Ports	4 - USB 3.0 A (9 pin; SuperSpeed) Female
OS Compatibility	OS Independent; No additional drivers or software required
Note	If used with the Apple Mac OS operating system, this device will function in USB 2.0 mode only
System and Cable Requirements	USB 3.0 or 2.0 or 1.x compliant host controller with available port.
LED Indicators	1 - Power (Blue)
Center Tip Polarity	Positive
Input Voltage	110 ~ 240 AC
Output Current	2A
Output Voltage	5 DC
Plug Type	Μ
Power Source	AC Adapter Included
Humidity	5~85% RH
Operating Temperature	0°C to 50°C (32°F to 122°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Shipping (Package) Weight	10.6 oz [300 g]
Included in Package	1 - USB 3.0 Hub
Included in Package	1 - USB 3.0 cable
Included in Package	1 - Power Adapter
Included in Package	1 - Instruction Manual
-	



### **Certifications, Reports and Compatibility**









www.startech.com/au 1800 808 346