

Spec Sheet

7-Port USB 3.0 Hub - Desktop

StarTech ID: ST7300USB3B



The ST7300USB3B USB 3.0 Hub lets you add seven external USB 3.0 ports to a computer from a single USB 3.0 host connection.

Offering data transfer rates up to 5 Gbps, the USB hub meets SuperSpeed USB 3.0 specifications and is backward compatible with USB 2.0 and 1.x devices.

Designed for easy port access when connecting or disconnecting devices, the hub features one-sided port orientation, with current overload detection and protection across all seven ports. The hub supports Plug-and-Play and Hot-Swap technologies, letting you switch and operate your connected devices without having to power down the host computer.

The USB hub is bus powered for use in environments where a power outlet may be unavailable, but is perfect for high-power USB devices when used with the included optional power adapter.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Applications

- Expand your system USB 3.0 capabilities with additional ports
- Make USB ports more accessible by positioning the hub anywhere within cable reach
- Extend the range of USB devices by having the hub act as a mid-point repeater
- Separate tightly packed USB ports, to better accommodate larger USB plugs or prevent overcrowding



Features

- Seven downstream USB 3.0 ports accessible from one side of the hub
- Compliant with SuperSpeed USB 3.0, with support for up to 5 Gbps
- Plug-and-Play and Hot-Swap compatible
- Backward compatible with USB 2.0 and 1.x devices
- Current overload detection and protection on each USB port
- USB bus powered, includes optional external power adapter for high-power USB devices
- Includes USB 3.0 A to B cable

www.startech.com/au 1800 808 346

Hard-to-find made easy®

Spec Sheet

Technical Specifications

| Warranty | 2 Years |
|--|---|
| Bus Type | USB 3.0 |
| Chipset ID | VLI - VL812 |
| Fast-Charge Port(s) | No |
| Ports | 7 |
| USB-C Device Port(s) | No |
| USB-C Host Connection | No |
| Maximum Data Transfer Rate | 5 Gbps |
| Type and Rate | USB 3.0 - 5 Gbit/s |
| Connector Type(s) | 1 - USB Type-B (9 pin) USB 3.0 Female |
| Connector Type(s) | 7 - USB Type-A (9 pin) USB 3.0 Female |
| OS Compatibility | OS Independent; No additional drivers or software required |
| Note | If connected to a USB 2.0 host port, performance may be limited |
| System and Cable Requirements Available USB 3.0 port | |
| LED Indicators | 7 - Hub Port Connection LEDs |
| Center Tip Polarity | Positive |
| Input Current | 1.3 A |
| Input Voltage | 100 ~ 240 AC |
| Output Current | 3 A |
| Output Voltage | 12 DC |
| Plug Type | Μ |
| Power Source | AC Adapter Included |
| Humidity | 5-95% RH |
| Operating Temperature | -2°C to 52°C (29°F to 125°F) |
| Storage Temperature | -20°C to 56°C (-4°F to 132°F) |
| Color | Black |
| Enclosure Type | Plastic |
| Form Factor | Desktop |
| Product Height | 0.9 in [23 mm] |
| Product Length | 6.8 in [172 mm] |
| Product Weight | 5.2 oz [148 g] |
| Product Width | 2.8 in [70 mm] |
| Shipping (Package) Weight | 19.7 oz [558 g] |
| | |



Hard-to-find made easy®

Spec Sheet

Included in Package1 - USB 3.0 HubIncluded in Package1 - USB 3.0 CableIncluded in Package1 - Universal Power Adapter (NA/JP, EU, UK, ANZ)Included in Package1 - Instruction Manual

Certifications, Reports and Compatibility





```
■
C €
F©
```