APCRBC133

RoHS

★★★★½ 4.5 (4) Write a review

- Genuine APC RBC(TM) are tested and certified for compatibility to restore UPS performance to the original specifications.

- Includes: All required connectors, Battery recycling guide, Installation guide, Metallic battery tray or enclosure, Reusable packaging

Technical Specifications

Input

Number of Power Cords	1

Batteries & Runtime

Battery type	Lead-acid battery
Battery mounting	Enclosed battery cartridge
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	432

Physical

Maximum Height	3.3inches (83MM, 8.3CM)
Maximum Width	8.5inches (216MM, 21.6CM)
Maximum Depth	13.5inches (343MM, 34.3CM)
Net Weight	26.37lbs. (11.96KG)
Shipping weight	27.78lbs. (12.6KG)
Shipping Height	6.0inches (152MM, 15.2CM)
Shipping Width	14.5inches (368MM, 36.8CM)
Shipping Depth	19.5inches (495MM, 49.5CM)
Color	Black
Units per Pallet	20.0

Environmental

Operating Temperature	32 - 104 °F (0 - 40 °C)
Operating Relative Humidity	0 - 95 %
Operating Elevation	0 - 10000ft (0 - 3048meters)
Storage Temperature	-15 - 45 °C
Storage Elevation	0 - 50000ft (0 - 15240meters)

Conformance	
Standard warranty	1 year repair or replace

Sustainable Offer Status	
RoHS	Compliant

SIGN UP FOR EMAIL

I'd like to receive news and commercial info from Schneider Electric and its affiliates via electronic communication means such as email. For more details, please read our Privacy Policy.

Email

I am a... ▼

OK

WHO WE ARE

About APC

Investor Relations

Careers

Sustainability

CONNECT WITH US

Press

APC Blog

Schneider Electric Data Center Blog

Contact Us

FIND A RESELLER

Zip/Postal Code   Find

CATALOG KEYCODE

Enter Key Code   Go