

8/16-Port Cat 5 High-Density Dual Rail LCD KVM Switch

ALTUSCN KL1508 / KL1516 LCD KVM Switch features independently retractable, dual slide 17" or 19" LCD monitor and keyboard with built-in touchpad. A single KL1508 / KL1516 can control up to 16 computers. For increased reliability and efficiency, RJ-45 connectors and Cat 5 cable are used to link to the computers. Utilizing KVM Adapter Cables for the final linkup, the KL1508 / KL1516 permits any combination of PCs, Macs, Sun computers, and serial devices to coexist on the installation.

17" or 19" LCD Option

- Super A-Grade TFT LCD Panel
- Zero Dead Pixel Guarantee*




Distance Extension – Up to 40 m via Cat 5 connection



Multiplatform Support – KVM adapter cables allow flexible interface combinations

Shared Access 2 Local Users	2nd Console PS/2	Computers PS/2, USB, Sun, Serial	OS Support Win, Mac, Linux, Unix, Sun, FreeBSD
Expansion Daisy Chain	LCD Monitor 17" / 19"	External Mouse PS/2	

Diagram



KVM Adapter Cables

KL1508/KL1516 provide a modular approach to server management.

Connect to devices with PS/2 ports	KA9520
Connect to devices with USB ports	KA9570
Connect to Sun Legacy systems (with 13W3 port)	KA9130
Connect to Sun USB systems	KA9131
Connect to Serial based devices	KA9140

Features

- Integrated KVM console with 17" or 19" LCD monitor in a Dual Rail housing
- A single console controls up to 8 (KL1508) or 16 (KL1516) computers
- KVM adapter cables* designed with automatic conversion to allow flexible interface combinations (PS/2, USB, Sun and serial) to control all computer types
- Multiplatform support: PC, Mac, Sun and Serial
- Extends the distance between computers and switch—up to 40 m (130') for resolutions of 1280 x 1024 @ 75Hz
- OSD tree structure makes finding and managing computers easy
- Conveniently located station and port selectors with 7-segment LED displays to quickly switch to target computers
- Dual Rail housing is slightly less than 1U with top and bottom clearance for smooth operation in 1U of rack space
- Extra console port—manage computers in the LCD KVM switch from an external console (monitor, PS/2 keyboard, and PS/2 mouse)
- Supports external PS/2 mouse
- Dual Rail—LCD monitor slides independently of the keyboard/touchpad
- Console lock—enables the console drawer to remain securely locked away in position when not in use
- Dedicated Hotkey Mode and OSD Invocation Keys reduce the number of keystrokes and provide quick access to these functions
- Daisy chain up to 31 additional KVM switches to control up to 512 computers
- Auto Scan Mode enables continuous monitoring of user-selected computers
- Two level password security—only authorized users view and control the computers—up to four Users plus an Administrator with separate profiles for each
- PS/2, USB, and Serial keyboard and mouse emulation—computers boot even when the console focus is elsewhere
- Firmware upgradable

Rack Mount Kit	Depth (cm)
2X-010G (Long) (Optional)	68 – 105
Short (Standard)	42 – 77

Easy Installation Rack Mount Kit	Depth (cm)
2X-012G (Long) (Optional)	17" LCD: 68 – 105 19" LCD: 74 – 105
2X-011G (Short) (Optional)	17" LCD: 67 – 70
	19" LCD: 63 – 70

Specifications

Function		KL1508	KL1516
Computer	Direct	8	16
Connections	Max.	256 (via Daisy Chain)	512 (via Daisy Chain)
Port Selection	OSD, Hotkey, Pushbutton		
	Connectors	External Console	1 x 6-pin Mini-DIN Female (Purple)
		Keyboard Video	1 x HDB-15 Female (Blue)
	Ports	Mouse	1 x 6-pin Mini-DIN Female (Green)
		KVM Ports	8 x RJ-45 Female (Black) 16 x RJ-45 Female (Black)
	Daisy Chain Ports	1 x DB-25 Male (Black)	
	F/W Upgrade	1 x RJ-11 Female (Black)	
	Power	1 x 3-prong AC Socket	
	External Mouse	1 x 6-pin Mini-DIN Female (Green)	
	Reset	1 x Semi-recessed Pushbutton	
Switches	Port Selection	2 x Pushbutton (Station); 2 x Pushbutton (Port)	
	Power	1 x Rocker	
	F/W Upgrade	1 x Slide	
	LCD Power	1 x Pushbutton	
LEDs	On Line		8 (Green) 16 (Green)
	Selected	Station ID	2 x 7-segment (Orange)
		Port ID	2 x 7-segment (Orange)
	Power	1 (Blue)	
	Lock	1 x Num Lock (Green) 1 x Caps Lock (Green) 1 x Scroll Lock (Green)	
LCD Power	1 (Orange)		
Emulation	Keyboard/Mouse	PS/2 ; USB(PC, Mac, Sun) ; Serial	
Video	17" LCD	1280 x 1024@75Hz	
	19" LCD	1280 x 1024@75Hz	
Scan Interval	1–255 Seconds		
I/P Rating	100–240V AC; 50/60 Hz; 1A		
Power Consumption	17" LCD	120V/ 28W; 230V/ 28W	
	19" LCD	120V/ 30W; 230V/ 30W	
Environment	Operating Temp.	0–40°C	
	Storage Temp.	–20–60°C	
	Humidity	0–80% RH, Non-condensing	
Physical Properties	Housing		
	Weight	17" LCD	17.30 kg
		19" LCD	18.50 kg
	Dimensions (L x W x H)	17" LCD	70.90 x 48.20 x 4.40 cm (19"/1U)
19" LCD		76.00 x 48.20 x 4.40 cm (19"/1U)	

* The specifications and pictures are subject to change Without notice.

* Please refer to www.ATEN.com for more details.